



Plymouth Rubber Europa, S.A.

TECHNICAL DATA SHEET

ADHESIVE TAPE **N-15**

MATERIALS

Backing (base) material Plasticized PVC film
 Colours Black, White, Grey, Red,
 Yellow, Brown, Green, Blue

DESCRIPTION AND FEATURES

- Tape with a good adhesion level.
- Meets the requirements of 2000/53/EC and RoHS 2002/95/EC Directives. Product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE).
- Meets EN 60454-3-1

TECHNICAL PROPERTIES

CHARACTERISTIC	TEST METHOD	SPECIFICATION	TYPICAL VALUE
Thickness (mm)	ASTM D-1000	0,18 ± 0,02	0,17
Width (mm)	"	Nominal ± 1	- - -
Adhesion to steel (N/cm)	"	Minimum 1,8	2,8
Adhesion to backing (N/cm)	"	Minimum 1,8	2,6
Breaking strength (N/cm)	"	Minimum 30	33
Elongation at break (%)	"	Minimum 170	220
Flammability	EN 60454-2	Flame retardant	Flame retardant
Dielectric breakdown (kV)	"	Minimum 7	8

FORM OF DELIVERY

Standard sizes: Length, 20 and 33 m
 Width, 19 and 25 mm
 Core diameter, 38 mm

Other sizes are available upon request.



Revised June 2012

Plymouth Rubber Europa, S.A.
 Ctra. Porriño-Salceda, km 1,5
 Apartado 12
 36400 PORRIÑO - SPAIN
 Tel.: +34 986 344 148
 Fax: +34 986 336 926